



# SOLAR MARQUISE

## NEWBUILD AND RESTORATION

### TECHNICAL CHARACTERISTICS

#### STRUCTURE\*

example for a Solar Marquise kit of up to 2 photovoltaic panels

#### Dimensions :

1 panel: 1,65 m x 0,90 m  
2 panels: 3,30 m x 0,90 m

#### Weight

For 1 panel:  
Structure=22kg  
PV panel+micro-inverter=24kg  
Total=46kg  
For 2 panels:  
Structure=41kg  
PV panels+micro-inverter=44kg  
Total=85kg

**Material :** steel

#### PHOTOVOLTAIC PANEL

#### Technology of the cells:

Silicium polycristallin ou monocristallin

**Appearance:** full black (frame and backing)

**Total power:** Our large format modules comprise of 260w maximum power output and 300w maximum output

\* The technical characteristics of the structure are given as a guide and can be adapted to your needs. For all projects, contact our hotline.



Available in 1 panel

THE  
PRODUCTS

- Architectural improvement
- Modern and attractive: black finish
- Comfort in summer
- Progressive solution
- Simple installation



# INSTALLATION



This diagram is not contractual. The dimensions are given as a guide and may change. For all projects, contact our hotline.

# RANGE OF ACCESSORIES

A complete range of specific finishing accessories:



SIDE SUPPORTS  
RIGHT AND LEFT

Dimensions :  
h 647 mm x l 951 mm  
unit weight: 2,4 kg

**THE FOR ARTISANS**

It takes less than an hour for two people to install the Solar Marquise !

**HOTLINE**

A team of experts to answer all your questions

[be.solaire@imerys.com](mailto:be.solaire@imerys.com)

**0 810 148 223** Service 0,15 € / min + prix appel